# DL7400

High Speed Printing
High Copy Ability
Straight Paper Path Route(Flat Bed)
Various Paper Path and
Several Paper Loading available
APTC and HCPP Function
Various Interface available

# Evolving towards perfection

Large Table and Rear Stacker
(optional)

DL7400

# FUJITSU

THE POSSIBILITIES ARE INFINITE

| | | | DL7400 |
|---|---|---|---|
| Printing Technology | | | Bi-directional with logical seeking in text and graphics mode |
| Print Head | | | 24 wire, Impact Dot Matrix |
| Printing columns (10cpi) | | | 136 column |
| Speed | Draft Quality | | 505cps (10cpi), 606cps (12cpi) *1 |
| | Report Quality | | 240cps (10cpi), 288cps (12cpi) |
| | Letter Quality | | 120cps (10cpi), 144cps (12cpi) |
| Resolution | | | 360 x 360 dpi (Maximum Graphics Resolution, Under ESC/P Emulation only) |
| Copy Ability | | | Original + 4carbonless copies (At High Copy Mode: Original + 7 carbonless copies) |
| Max. paper thickness | | | 0.57mm (0.2244") |
| Paper feeding | Continuous Form | | Push tractor - Front in, Rear out ; Rear in , Front out |
| | Cut Sheet | | Front in, Front out ; Front in, Rear out ; Rear in, Front out ; Rear in, Rear out |
| Line Feed Speed | | | 60ms per 1/6" line |
| Form Feed Speed | | | 6" per second continuous feed |
| Continuous Form/Cut Sheet switch function | | | Manual/Auto |
| Paper thickness adjust function | | | Manual/Auto |
| Paper | Cut Sheet | Width | 55~420mm (2.2 ~ 16.5 inch) |
| | | Length | 70~297mm (2.76~11.69 inch), (70~420mm (2.76~16.5 inch) for Large Cut Sheet Table) |
| | Continuous Form | Width | 102~420mm (4.0~16.5 inches) |
| | | Length | Over 102mm (Over 4.0 inches) |
| Interface | Parallel | | IEEE1284 Nibble Mode |
| | USB | | USB Ver.1.1 (TYPE B) |
| | Serial | | RS232C 25pin |
| LAN (Optional card needed) | | | 10BASE-T, 100 Base-TX , TCP/IP Protocol, |
| Emulation | | | Fujitsu DPL24C PLUS, Epson ESC/P2, IBM ®XL24E, |
| Character Sets | | | Code pages 437, 850, 851, 852, 855, 860, 862, 863, 865, 866, ISO 8859-1,ECMA 94, USA, UK, German, French, Italian, Spanish, Swedish, Finnish, Norwegian, Danish 1 and 2, Hungarian 1 and 2, Slovenian 1 and 2, Mazowia 1 and 2, Polish 1 and 2, Latin 2 1 and 2, Latin P, PG-DHN, Elot 927, Lithuanian 1 and 2, Mik, Macedonian, PG-MAC, ABY, ABG, DEC GR, GREEK 11, HBR-OLD, HBR-DEC, ISO Turkish, ISO Latin, Kamenicky 1 and 2, Turkish 1 and 2, Elot 928, Cyrillic, RUSCII, Latin-9, Spanish1, Spanish2, Japan, Latin A, KOREA, LEGAL, Windows Code Page 1250, Windows Code Page 1251, Windows Code Page 1252, IBM437, IBM851 |
| Barcode | | | Code 3 of 9, UPC Type A, UPC Type A with check character, Codabar(NW7), EAN13, EAN8, Industrial 2 of 5, Matrix 2 of 5, Interleaved 2 of 5, Code 128 |
| Resident Fonts | | | Bitmap font : Courier 10, Prestige Elite12, Boldface PS, Compressed, Draft 12, High-speed draft 12, OCR-B 10, OCR-A 10, Correspondence 10, PICA10<br>Scalable font : Courier, Nimbus Sans®, Timeless (Normal, Bold, Italic) |
| Input Buffer | | | Max. 128KB |
| Input Voltage | | | 100V AC to 120V AC ±10%, single phase, 50Hz to 60Hz<br>220V AC to 240V AC ±10%, single phase, 50Hz to 60Hz |
| Consumption Power | Waiting | | 10W or less |
| | Average | | 90W or less |
| | Max. | | 180W |
| Environmental Conditions | | | 5℃ to 38℃ (41℉ to 100℉), 20~80%RH |
| Dimension | (WxDxH) | | 600 x 350 x 290mm (23.62 x 13.78 x 11.42inch) |
| Weight | | | Approximately 17Kg (37lbs) |
| Noise | | | 59dBA |

| Model | Parallel + USB Model (LAN Upgradeable) |
|---|---|
| | Parallel + RS232C Model |

| Option | Cut Sheet Feeder (should be used with Rear Stacker) |
|---|---|
| | LAN Card |
| | Rear Stacker |
| | Large Cut Sheet Table |
| | Tractor |

| Reliability | MTBF | 20,000H(25% duty cycle) |
|---|---|---|
| | MTTR | 0.5H |
| | Printer Life | 5 million Line-Feed or 5 years |
| Print Head | Print Head Life | 400million strokes (each wire) |
| Ink Ribbon | Ribbon Life (Black) | 5 million characters (ANK Draft Quality) |
| Safety and EMI standard | | For Europe , North America and Asia Pacific |
| Environment | Fujitsu Green Product | Conformance |

*1 Some letters cannot be printed at this speed. (505CPS at 10CPI)

◆**High Speed Printing**
High Speed Printing as 606cps (12cpi,Draft Quality)

◆**High Copy Ability**
Maximum original +7 multiple copy sheet is able to be printed

◆**Straight Paper Path Route (Flat Bed)**
The Straight Paper Path Route enables paper to be fed smoothly. As paper does not need to be bent, there will be no discrepancy between top sheet and bottom sheet of multiple copy sheet and LF Accuracy is improved.

◆**Various Paper Path & Several Paper Loading available**
8 paper paths are available, of which up to 4 paper can be loaded at the same time. Utilising multiple paper paths enables various kinds of paper usage in a limited paper setting area and limited paper out condition.

Various Paper Paths          Several Paper Loading

◆**APTC and HCPP Function**
Detecting paper thickness, adjusting Head Gap automatically (APTC) ,and changing paper paths can be handled through the host by using Application Software or Windows Driver even if several paper forms are loaded at the same time.(HCPP)

◆**Various Interface available**
Parallel,RS232C,USB Interface and Optional LAN Card available

## Fujitsu Worldwide

06.11-01